

**For the best connection:**

The blaugelb Pressure Roller improves the adhesion of the foil to the substrate



## blaugelb Pressure Roller

For the efficient processing of blaugelb foils.

**Product features:**

The blaugelb Pressure Roller is the ideal tool for the fast and reliable processing of the foils. It is built to be sturdy and durable for everyday use and equipped with all features for convenient work.

When bonding foils, such as at the connecting joint of windows and doors, it is important for the foil to establish a good adhesive bond with the substrate if a lasting sealing effect is to be guaranteed (follow the processing information for the products). This requires the foils to be pressed firmly against the substrate. That's where the specially optimised properties of the blaugelb Pressure Roller come into their own.

For efficient processing of the foils, the blaugelb Pressure Roller has a sturdy, solid wooden handle and a torsionally rigid steel bracket, ensuring that the pressure is transferred directly with less effort. The ergonomically shaped handle ensures a secure grip so it does not slip from the hand, taking the fatigue out of the job.

- Robust design
- Angled, one-sided roller holder for ease of use in corners
- Sturdy, galvanized steel bracket
- Smooth-running roller
- Cylindrical roller made of 8 mm thick hard rubber
- Made in Germany



The angled, one-sided steel bracket means that the foil can be pressed firmly against the substrate right into the corners. That improves adhesion even at hard-to-reach places, ensuring a lasting sealing effect. The rubber roller is very strong, but still elastic enough for fluid rolling, which enhances comfort in use and allows the foil to be adapted easily to the contours of the substrate. The diameter of the rubber roller makes it ideal for efficient rolling, while the smooth-running axle removes the need for tilting.

Technical data:

Dimensions:	L 18.5 cm x W 6.2 cm x H 3.0 cm
Weight:	120 grams
Application:	Pressing foils when bonding to a substrate
Handle:	Solid wooden handle, painted, ergonomically shaped, blue, with sturdy, galvanized steel bracket
Rubber roller:	Hard rubber, cylindrical Thickness 8 mm Width 45 mm Diameter 30 mm

Product name	PU	Item no.
blaugelb Pressure Roller	6 pieces	9074068

Preparation and processing:

The blaugelb Pressure Roller is suitable for all foils, whether or not they can be plastered over and whether or not they have a self-adhesive strip. We particularly recommend using the blaugelb Pressure Roller when bonding the blaugelb All-Weather Foil as well.

Prepare the substrate for proper bonding (finish smooth, clean, note the requirements for proper bonding). If necessary, use the appropriate primer as well. Attach the foil using foil adhesive or the self-adhesive strip in accordance with the processing instructions in the relevant technical data sheet.

Then roll the blaugelb Pressure Roller firmly back and forth over the foil several times, pressing the foil thoroughly against the substrate (e.g. window frame and masonry) and going into the corners as well. If bonding the foil using foil adhesive, make sure that the adhesive bead has the necessary coat thickness. Where necessary, make sure that the expansion loop of the foil goes right into the corners. Also press the blaugelb Pressure Roller down firmly where the foil overlaps.

After processing, clean the blaugelb Pressure Roller to prevent crusting and maintain its function and service life over the long term. We recommend cleaning with blaugelb Cleaning Cloths in the practical dispenser (item no. 0241602). They reliably remove fresh sealant and adhesive residues and other contamination.

For further information about processing foils, in addition to the relevant product data sheets we also recommend technical bulletin no. 5 “Verputzen von Fensteranschlussfolien” [Plastering of Window Connecting Foils] issued by the Federal Finishing & Façade Association confederated in the German Construction Industry Association (ZDB) and the Construction Gypsum Industry Group in the Bundesverband der Gipsindustrie e.V.

Storage and form of delivery:

The blaugelb Pressure Roller is supplied in boxes of 6. Storage between +5 °C and +25 °C. Protect against heat, moisture and frost.

Disposal:

The disposal conforms with the national specifications.

Safety note:

Only for trade use.